

OVERVIEW

Item No.	Model	Description	max. Baud Rate	Feature	Software	Note
Serial						
113303	I-7510 CR	RS-485 Repeater	115.2 kbps	Auto baud & Auto direction (RS-485)	independent	2-wire operation
113304	I-7510A CR	RS-422/485 Repeater				2- and 4-wire operation
113904	I-7510AR CR					
113956	I-7551 CR	RS-232 Isolator	115.2 kbps	Auto baud, handshake with CTS, RTS	independent	Isolation 3750 V port to port
113305	I-7513 CR	RS-485 to 3 x RS-485 Hub	115.2 kbps	3-port Hub	independent	RS-485 input: isolated, 3000 V
124220	I-7514U-G CR	RS-485 to 4 x RS-485 Hub	115.2 kbps	4-port Hub	independent	Channel 1 to 4: isolated, 2500 V
CAN						
118402	I-7531-G CR	CANbus Repeater	800 kbps	isolated CAN segments	-	Isolation 2500 Vrms between 2 CAN ports
126673	I-2534 CR	CANbus Hub	1 Mbps	star or tree topology	Configuration utility	4 CAN-ports
120374	I-7532-G CR	CANbus Bridge	1 Mbps	CAN segments with different baud rates	Baud rate per switch	Isolation 2500 Vrms between 2 CAN ports
USB						
122687	USB-2560 CR	USB Hub	480 Mbps	4 x USB 2.0 Type A	independent	Supports high speed and full speed

