

OVERVIEW

Item No.	Model	Ports	Speed	Type	Connector	Operating Temp.	Note
Unmanaged, standard							
117857	NS-205 CR	5	10/100 Mbit	Twisted pair	RJ45	-40°C to +75°C	-
113245	NS-208 CR	8					
114576	NS-208G CR	8	Gigabit	Twisted pair	RJ45	-40°C to +75°C	-
122540	NS-205G CR	5					
130173	NS-205AG CR						
127053	NS-208R CR	8	10/100 Mbit	Twisted pair	RJ45	-40°C to +75°C	Suitable for railway use (EN 50155)
121658	NS-205R CR	5					
121346	NS-205A CR	5	10/100 Mbit	Twisted pair	RJ45	-40°C to +75°C	12 to 56 VDC
127051	NS-208A CR	8					12 to 48 VDC
126097	IES-1240	24	10/100 Mbit	Twisted pair	RJ45	-40°C to +70°C	IP30 metal chassis
126096	IES-1160	16					
119877	IES-1050A	5	10/100 Mbit	Twisted pair	RJ45	-40°C to +70°C	Slim design, IP30 metal chassis
119878	IES-1080A	8					
123683	IGS-1050A	5	Gigabit	Twisted pair	RJ45	-40°C to +70°C	Slim design, IP30 metal chassis
126089	IGS-1080A	8					
Unmanaged, with fiber optics							
114813	JetNet 3010G	7+3	7 x 10/100 Mbit	Twisted pair fiber, SFP	RJ45 RJ45/SFP Combo	-20°C to +70°C	Redundant voltage supply
124633	JetNet 3010G-w		3 x Gigabit			-40°C to +70°C	
128447	JetNet 3008f-m V3	6+2	6 x 10/100 Mbit	Twisted pair fiber, multi mode	RJ45 SC	-10°C to +70°C	Redundant voltage supply
128314	JetNet 3008f-mw V3		2 x 10/100 Mbit			-40°C to +75°C	
119738	JetNet 3008f-s V3		6 x 10/100 Mbit	Twisted pair fiber, single mode	RJ45 SC	-10°C to +70°C	
128315	JetNet 3008f-sw		2 x 10/100 Mbit			-40°C to +75°C	
114577	NS-205FT CR	4+1	4 x 10/100 Mbit	Twisted pair fiber, multi mode fiber, single mode	RJ45, ST	0°C to +70°C	Redundant voltage supply
114575	NS-205FC CR		1 x 100 Mbit		RJ45, SC		
114669	NS-205FCS CR				RJ45, SC		
115836	NS-206FT CR	4+2	4 x 10/100 Mbit	Twisted pair fiber, multi mode fiber, single mode	RJ45, ST	0°C to +70°C	Redundant voltage supply
115837	NS-206FC CR		2 x 100 Mbit		RJ45, SC		
114526	NS-206FCS CR				RJ45, SC		
121671	NS-209FT CR	8+1	8 x 10/100 Mbit 1 x 100 Mbit	Twisted pair fiber, multi mode fiber, single mode	RJ45, ST	0°C to +70°C	Redundant voltage supply
121672	NS-209FC CR				RJ45, SC		
121673	NS-209FCS CR				RJ45, SC		
129250	NS-205AFT-T CR	4+1	4 x 10/100 Mbit 1 x 100 Mbit	Twisted pair fiber, multi mode fiber, single mode	RJ45, ST	-30°C to +75°C	Slim design
129251	NS-205AFC-T CR				RJ45, SC		Slim design, distance 30 km
129252	NS-205AFCS-T CR			RJ45, SC	Slim design, distance 60 km		
129253	NS-205AFCS-60T CR			Twisted pair, fiber, sm	RJ45, SC		
129156	NS-206AFT-T CR	4+2	4 x 10/100 Mbit 2 x 100 Mbit	Twisted pair fiber, multi mode fiber, single mode	RJ45, ST	-30°C to +75°C	Slim design
129106	NS-206AFC-T CR				RJ45, SC		Slim design, distance 30 km
129107	NS-206AFCS-T CR			RJ45, SC	Slim design, distance 60 km		
129108	NS-206AFCS-60T CR			Twisted pair, fiber, sm	RJ45, SC		
Unmanaged, with Power over Ethernet (PoE)							
120923	NS-205PSE CR	5	5 x 10/100 Mbit, davon 4 x PoE	Twisted pair	RJ45	-40°C to +75°C	PoE (802.3af)
123629	NS-205PSE-24V CR						PoE (802.3af), 24 V Boost
123092	NS-208PSE CR	8	10/100 Mbit	Twisted pair	RJ45	-40°C to +75°C	PoE (802.3af), slim design
123093	NSM-208PSE CR		Gigabit				PoE (802.3af), IP30 metal chassis
126120	IGPS-1080A	8	Gigabit	Twisted pair	RJ45	-40°C to +70°C	PoE+ (802.3at)
126121	IGPS-1080-24V						PoE+ (802.3at), 24 V Boost
Unmanaged, with PoE & fiber optics							
124598	NS-205PFT CR	4+1	4 x 10/100 Mbit 1 x 100 Mbit	Twisted pair fiber, multi mode	RJ45, ST	-30°C to +75°C	PoE (802.3af)
124599	NS-205PFC CR				RJ45, SC		PoE (802.3af)
124600	NS-205PFCS CR			Twisted pair fiber, single mode	RJ45, SC		PoE (802.3af), distance 30 km
124601	NS-205PFCS-60 CR				RJ45, SC		PoE (802.3af), distance 60 km
142088	NSM-205GP CR	4G+1G	4 x Gigabit 100 Mbit/Gigabit	Twisted pair fiber, SFP-Port	RJ45	-40°C to +75°C	PoE+ (802.3at), IP30 metal chassis, redundant voltage supply

OVERVIEW

Item No.	Model	Ports	Speed	Type	Connector	Operating Temp.	Note	
Managed, standard								
125552	JetNet 4508 (V2)	8	10/100 Mbit	Twisted pair	RJ45	-25°C to +70°C	Super Ring, Web, CLI, Telnet, SNMP	
128310	JetNet 4508w (V2)					-40°C to +75°C		
Managed, with fiber optics								
128469	JetNet 4508f-m (V2)	6+2	6 x 10/100 Mbit 2 x 100 Mbit	Twisted pair fiber, multi mode	RJ45, SC	-25°C to +70°C	Super Ring, Web, CLI, Telnet, SNMP	
128251	JetNet 4508f-mw (V2.2)			-40°C to +75°C				
128470	JetNet 4508f-s (V2)			Twisted pair fiber, single mode	RJ45, SC	-25°C to +70°C		
128311	JetNet 4508f-sw (V2)			-40°C to +75°C				
118372	JetNet 4510	7+3	7 x 10/100 Mbit 3 x 10/100 Mbit	Twisted pair fiber, SFP	RJ45	-25°C to +70°C	Super Ring, Web, CLI, Telnet, SNMP	
125760	JetNet 4510-w			RJ45/SFP Combo	-40°C to +75°C			
114812	JetNet 5010G	7+3G	7 x 10/100 Mbit 3 x 100 Mbit / Gigabit	Twisted pair fiber, SFP	RJ45	-25°C to +70°C	Super Ring, Web, CLI, Telnet, SNMP	
128308	JetNet 5010G-w			RJ45/SFP Combo	-40°C to +75°C			
125100	JetNet 6059G	4G+5G	4 x Gigabit 5 x Gigabit	Twisted pair fiber, SFP	RJ45	-25°C to +70°C	Super Ring, Web, CLI, Telnet, SNMP, Full Gigabit	
125524	JetNet 6059G-w			RJ45/SFP Combo	-40°C to +75°C			
Managed, with PoE & fiber optics								
128317	JetNet 5310G	8+2G	8 x 10/100 Mbit 2 x 100 Mbit / Gigabit	Twisted pair fiber, SFP	RJ45 RJ45/SFP Combo	-40°C to +75°C	Super Ring, Web, CLI, Telnet, SNMP, PoE+ (802.3at)	
Rack, managed, with fiber optics								
123021	JetNet 5628G	24+4G	24 x 10/100 Mbit or 18 x 100 Mbit 4 x Gigabit Combo	Twisted pair fiber, RJ45/SFP Combo	RJ45 RJ45/SFP Combo	-40°C to +85°C	Modular, 3 x power, redundant	Power substation, suitable for railway use
124629	JetNet 5628G-2AC						Modular, 2 x 85-264 VAC	
127728	JetNet 5828G						Modular, 3 x power, redundant	
147653	JetNet 6528Gf-AC-DC24	16G+12G	16 x Gigabit 8 x Gigabit 4 x 100 Mbit / Gigabit	Twisted pair Twisted pair/fiber fiber, SFP	RJ45 RJ45/SFP Combo	-40°C to +75°C	AC and 24VDC, power substation, suitable for railway use	
142083	JetNet 6852G	48G+4G	48 x Gigabit 4 x Gigabit	Twisted pair fiber, SFP	RJ45 SFP slot	-10°C to +55°C	Layer 3, metal chassis	100-240 VAC
142085	JetNet 6852G-DC48						48 VDC	
142086	JetNet 7850G-2XG	48G + 2 x 10G	48 x Gigabit 2 x 10 Gigabit	Twisted pair fiber, SFP	RJ45 SFP slot	-10°C to +55°C	10G uplink ports, Layer 3, metal chassis	100-240 VAC
142087	JetNet 7850G-2XG-DC48						48 VDC	

